COMPAGNIE TUNISIENNE DE FORAGE

19 RUE DE L'ARTISANAT CHARGUIA II – 2035 L'AEROPORT-ARIANA TUNISIA FAX N°(216-70) 836 568/837 041 PHONE N°(216-70) 837 322

FAX MESSAGE

FROM : C.T.F

FAX REF: ATT: : RENTAL MANAGER

DATE : 23-01/2025 FAX N• : E-mail

CONTACT NAME: Y/REF : Page (01) of (05) including this page COPY :

SUBJECT: PP 25-58: SUPPLY ON RENTAL BASIS FOR THE FOLLOWING LOTS OF WELL CONTROL EQUIPMENT:

Lot 1: Double rams BOP 13"5/8 x 5K type U or equivalent

Lot 2: Annular BOP 13"5/8 x 5000 psi

Compagnie Tunisian de Forage, (CTF) is now seeking competitive bids for the supply on Rental Basis of 2 lots of well control equipment.

To this purpose you are hereby invited to submit your best prices and delivery in full compliance with the following terms and conditions.

A - SCOPE OF WORK:

Supply on rental basis of the following well control equipment to meet the minimum technical requirements detailed in **Attachment A**.

B-Estimated rental period:

For Lot 1 50 days about + transit time (Rental start date: mid-February)
For Lot 2: 50days activity+ transit time (Rental start date: mid-February)
Stand by rate "50%" will be applied at time of transport.

C – DELIVERY REQUIREMENT

The delivery shall not exceed 15 days from date of signature of PO, evidenced by date of "CMR" if transport is arranged by the bidder.

D - ACKNOWLEDGEMENT:

You are kindly requested to acknowledge receipt of this inquiry by return fax.

E - BID CLOSING DATE:

Bids must be sent no later than <u>January 29th, 2025.</u> as per bid submission instructions here in after.

F - FORM OF BIDS:

Bids shall be in the form of proforma invoices as per the formats shown under $Attachment\ B$ and shall include all requested details.

G-VALIDITY:

Bids shall be valid for a period of at least 90 days from bid closing date.

H/BID SUBMISSION PROCEDURE:

Bids shall be submitted by e-mail to: <u>Closed.bids@ctf.com.tn</u> as per the pro forma provided under

I - CONTACTS:

Any further information or clarification required during the bidding period to aid bidder in the preparation of his bid shall be requested in writing by fax addressed to:

COMPAGNIE TUNISIENNE DE FORAGE FAX N° (216-70) 837 041 – 836 568 ATT: TENDER BOARD

J - SPECIAL NOTES:

- The financial offers for each lot and after the correction of possible errors of calculation, will be classed from the lowest bidder to the highest bidder and CTF will select the best discounted offers which meet CTF technical (Based on provided of the requested technical documentation in Attachment A for each lot).

BEST REGARDS,

C.T.F.

PROCUREMENT & MARKETING DEPARTMENT

ATTACHMENT A MINIMUM TECHNICAL SPECIFICATIONS

Lot N1: Double rams BOP 13"5/8 x 5K type U or equivalent

Bore size: 13"5/8

Pressure rating: 5000 PSI

H2S Trim (Nace MR0175)

Top connection and Ring grove API 13"5/8 x 5000 PSI (BX160) flanged or studded

Bottom connection and Ring grove API 13"5/8 x 5000 PSI (BX160) flanged or studded

At least two flanged outlets in the lower cavity; all outlets must be plugged. Lower cavity outlets must be 3"1/8 5K and 2"1/16 5K.

Complete with: * blind shear rams in the upper cavity

* Large bore bonnet (without tandem booster) in the upper stage. If the provider can give evidence (calulation) that the Bop is able to shear DP 3"1/2 G105 #13.3 with standard bonnet, it can be accepted

- * variable rams 2"7/8 5" in the lower cavity
- * Certified lifting points

A set of rubbers must be provided for each set of ram for eventual use (only utilized rubbers will be charged)

- * Overall height of the BOP must not exceed 1,45 m
- * Overall length of the BOP with bonnets closed and locking screws locked must not exceed 3,2 m

Required documentation:

- Original certificate of conformance of the BOP, rams according to API 16A if available
- If original CoC is expired, a recertification certificate according to OEM, API STD 16AR and API STD 53 must be provided.
- CoC must be valid for minimum one more year
- Yearly inspection and test reports
- Pressure test reports not older that three weeks at low pressure (200 300 PSI) and maximum working pressure for BOP lower and higher cavities at low and high pressure
- Lifting points inspection reports not older than 3 months
- User manual +dimensional data
- Shearing capability to shear DP 3"1/2 G105 #13.3

Lot N2: Annular BOP 13"5/8 x 5K

Bore size: 13"5/8

Pressure rating: 5000 PSI H2S Trim (Nace MR0175)

Top connection and Ring grove API 13"5/8 x 5000 PSI (BX160) studded

Bottom connection and Ring grove API 13"5/8 x 5000 PSI (BX160) flanged

Complete with certified lifting points

A new packing unit will be provided as spare and will be charged to CTF only if used

* Overall height of the BOP must not exceed 1,40 m

Required documentation:

- Original certificate of conformance of the BOP, rams according to API 16A if available
- If original CoC is expired, a recertification certificate according to OEM, API STD 16AR and API STD 53 must be provided.
- CoC must be valid for minimum one more year
- Yearly inspection and test reports
- Pressure test reports not older that three weeks for the BOP at low pressure (200 300 PSI) and maximum working pressure
- Lifting points inspection reports not older than 3 months
- User manual +dimensional data

ATTACHMENT B

Financial OFFER

PRO-FORMA INVOICE FORMAT USING YOUR COMPANY LETTER HEAD

FROM: BIDDER'S FULL NAME: ADDRESS: TELEPHONE N°: FAX N°: CONTACT NAME: PRO-FORMA INVOICE			TO: COMPAGNIE TUNISIENNE DE FORAGE 19 RUE DE L'ARTISANAT 2035 CHARGUIA II ARIANA – L'AEROPROT TUNIS - TUNISIA			
DATE :						
Lot	Qty	DESCRIPTION	Operating Price /day		Stand By Price /day	
			withholding TAX Excluding Including		withholding TAX Excluding Including	
			Excluding	15%	Excluding	15%
01	1	Double rams BOP 13"5/8 x 5K type U or equivalent				
02	1	Annular BOP 13"5/8 x 5000 psi				
Post Payn Note At th	rental insp nent terms: : ee moment (ese equipment "for each lot" from your yand ection for each lot:	ll be fixed basi here your ban	s on the conv	vention betwee	
1	<i>NAME :</i>		SIGNATURE :			
TITLE :			DATE:			
		COMPANY-STAM	P			